

Aluminum Terminal Lugs

AR's Aluminum Terminal Lugs are high-quality, high-performance products made from 99.5% pure aluminum. They feature a seamless, one-piece design and undergo a chemical treatment for an enhanced finish. With a high conductivity level of over 58% IACS, they ensure efficient power transmission. Each lug is marked with detailed specifications for easy identification. The manufacturing process complies with **DIN EN 755-7** standards.



Conductor Size	Stud Siz	Con. Die D	A	B	C1	C2	D1	D2	D2
25	M8	12	39	18	9.5	12	6.8	12	60
35	M10	14	42	21	11.2	14.5	8	14	67
50	M10	16	44	25	14	14.5	10	16	72
70	M12	18	51.5	28	15	17.5	11.2	18	86
95	M12	22	51.5	32	15.5	18	13.2	22	90
120	M12	22	51.5	32	16	17	14.7	22	91
150	M12	25	59	35	17.5	21.5	16.3	25	103
185	M16	28	59	40	21.5	25	18.5	28	106
240	M16	32	67	45	23.5	26	21	32	116
300	M16	34	76.5	49	24	25	23.3	34	124
400	M20	38	99	58	30.5	32	26	38	165
500	M20	44	110	60	30	31.5	29	44	185

FOR ENGINEERING SUPPLIES

DAR