

C-Clamp

DAR's Earthing C-Clamp is a premium grounding solution, engineered to establish a firm connection between an electrical conductor and the earth. It is constructed from copper, with the flexibility to opt for tinned copper as per customer preferences, thereby accommodating a broad spectrum of customer requirements.

Code	Main Conductor	Conductor Range
DAR-CC101510	10 mm ²	1.5 – 10 mm ²
DAR-CC161516	16 mm ²	1.5 – 16 mm ²
DAR-CC16251510	16 - 25 mm ²	1.5 – 10 mm ²
DAR-CC251625	25 mm ²	16 – 25 mm ²
DAR-CC351516	35 mm ²	1.5 – 16 mm ²
DAR-CC352535	35 mm ²	25 – 35 mm ²
DAR-CC50425	50 mm ²	4 – 25 mm ²
DAR-CC503550	50 mm ²	35 – 50 mm ²
DAR-CC701525	70 mm ²	1.5 – 25 mm ²
DAR-CC5070435	50 – 70 mm ²	4 – 35 mm ²
DAR-CC50703570	50 – 70 mm ²	35 – 70 mm ²
DAR-CC95435	95 mm ²	4 – 35 mm ²
DAR-CC953570	95 mm ²	35 – 70 mm ²
DAR-CC957095	95 mm ²	70 – 95 mm ²
DAR-CC12025120	120 mm ²	25 – 120 mm ²
DAR-CC15025120	150 mm ²	25 – 120 mm ²
DAR-CC15070150	150 mm ²	70 – 150 mm ²
DAR-CC1851695	185 mm ²	16 – 95 mm ²
DAR-CC120185120185	120 – 185 mm ²	120 – 185 mm ²
DAR-CC15024095120	150 – 240 mm ²	95 - 120 mm ²



DAR
FOR ENGINEERING SUPPLIES